

ENCIRCLED FLUX (EF) TEST SOLUTIONS

SPSB-EF LAUNCH MODE CONDITIONNER AND FLS-600-NS1548 LIGHT SOURCE
DESIGNED FOR CONTROLLED MULTIMODE LOSS TESTING



Tier-1/2 solutions with controlled source launch conditions for maximum accuracy and repeatability designed to remove uncertainty from multimode fiber testing.

KEY FEATURES

EF-compliant as per TIA -526-14-B and IEC 61280-4-1 Ed. 2.0

Optimized for multimode loss testing

Tier-1/2 testing of multimode fibers as recommended in TIA-568

Reference-grade UPC connectors for maximum precision and repeatability

Built-in-EF-compliant light source – no extra equipment to manipulate

APPLICATIONS

Data center/high-speed links

Enterprise and private networks

COMPLEMENTARY PRODUCTS AND OPTIONS



AXS-110



FLS-140



FastReporter2 Data
Post-Processing Software



UNDERSTANDING EF

Encircled Flux (EF) is a new standard that defines how to control the source launch conditions as specified in TIA-526-14-B and IEC 61280-4-1 Ed. 2.0.

Whether for an expanding enterprise business or a large-volume data center, the new high-speed data networks built with multimode fibers are running under tighter tolerances than ever before.



These MM fibers are the trickiest links to test because the results depend greatly on each device's output conditions. Testing with different equipment often returns different test results, sometimes higher than the budget loss itself. This may mislead the technician or make it impossible to locate the fault, resulting in unsuccessful turn-ups or a longer network downtime. Now, cable installers can rely on their Tier-1 loss results and Tier-2 troubleshooting can be performed with maximum accuracy and utmost confidence of finding the actual problem.



CONSISTENCY AND REPEATABILITY

Whether built-in or packaged in the external launch conditioner, EXFO tunes each EF-compliant device to perfection in-house, ensuring that every unit meets the EF templates for both 850 and 1300 nm at 50 μm . This allows technicians and contractors to obtain reliable, consistent and repeatable results during construction, thus eliminating doubts and uncertainty. The test documentation that is generated will also help future-proof networks. When upgrades are needed, it will become easier and faster to know which circuits have to be activated, thereby saving time and troubles down the line.

TWO FIELD SOLUTIONS TO CHOOSE FROM

| | MULTIMODE LIGHT SOURCE FOR CONSTRUCTION (TIER-1 BASIC) | MULTIMODE OTDR FOR TROUBLESHOOTING (TIER-2) |
|------------------------------------|---|--|
| |  |  |
| EF-Compliant Test Solutions | FLS-600-NS1548 | FLS-600 |
| EF Launch Conditions | Built-in with reference grade jumper | Paired with External Mode Conditioner (SPSB-EF-C30) |
| Key Benefit | <ul style="list-style-type: none"> > No extra tool to carry > No need to use mandrels | <ul style="list-style-type: none"> > Leverage your existing FLS-600 > Get EF compliance with low cost of ownership |
| Results | Accurate and repeatable insertion loss (IL) measurement for successful turn-ups | Undoubtful and accurate fault location for quicker link repair, reducing mean time to recovery (MTTR) |
| Description | Like all EXFO portable instruments, the FLS-600 is built for the harshest test conditions. It features a keypad with LCD backlight, for easy operation in darker environments. Combined with an FPM-600 power meter, it automatically selects the testing wavelengths and sends the reference power value to ensure accurate results. | Packaged in a soft, light and convenient carrying case, it is compatible with EXFO OTDRs and the FLS-600 series. It includes 30 m of fiber to be used as a launch cable with OTDR. |
| Key Features | <ul style="list-style-type: none"> > EF-compliant for basic Tier-1 certification > Four wavelengths on two ports: 850/1300 nm and 1310/1550 nm > 3-year warranty for low cost of ownership > Error-free, time-saving test features | <ul style="list-style-type: none"> > Covers OTDR dead zones, enabling loss measurement on the first and last connections of a fiber under test > Increases the life of the source connector by reducing the number of matings on the connector > Supports LC/UPC and SC/UPC connectors |
| Outcome | Build and maintain a future-proof multimode fiber network with utmost reliability and accuracy. | |


Note: EF-compliant launch conditions with SPSB-EF external launch conditioner can only be achieved when paired with EXFO products as listed in this table. This may not be possible with OTDRs or light sources from other manufacturers.

THE NECESSITY OF LAUNCH AND RECEIVE CABLES

Link characterization is often performed using an OTDR. However, despite the fact that an OTDR has the shortest dead zones, the way loss is measured in a link means that to characterize the first and last connectors, an OTDR needs a launch cable, also called a pulse suppressor box.

The reason for this is that the loss associated with an event is the difference between the backscattering levels measured before and after the event. To account for the dead zone, a backscattering level must be obtained before the first connector. This requires inserting a length of fiber between the OTDR port and the first connector of the fiber under test. At the other end, the same length of fiber is inserted after the last connector.

In order to measure the loss of the first and last connectors, it is important to use launch and receive cables. The SPSB-EF has an internal 30-meter fiber that allows complete end-to-end loss while still maintaining the EF launch conditions up to the first connector of the link. By complying with the EF standards, faulty connectors are easily located when troubleshooting high-speed multimode links.



NOTE: To measure the loss in the first connector with the SPSB-EF launch cable, the OTDR pulse width should be 100 ns or shorter and the connection to the OTDR port should have a reflection value of -45 dB or better. A 50 μ m test link must also be selected.

SPECIFICATIONS FLS-600-NS1548 ^a

| Model | 12C | 23BL |
|---|---|------------------------|
| Central wavelength (nm) | 850 ± 25 1300 +50/-20 | 1310 ± 20 1550 ± 20 |
| Spectral width ^{b,f} (nm) | 50/135 | ≤5 |
| Launch conditions ^f | Encircled flux compliant at 850 nm (guaranteed) at 1300 nm (typical) | |
| Auto-switching | Yes | Yes |
| Tone generation | 270 Hz, 1 kHz, 2 kHz | 270 Hz, 1 kHz, 2 kHz |
| Battery life (hours) (typical in Auto mode) | 50 | 50 |
| Warranty (years) | 3 | 3 |

GENERAL SPECIFICATIONS

| | | |
|-------------------------------------|------------------------------------|---|
| Size (H x W x D) | 190 mm x 100 mm x 62 mm | (7 1/2 in x 4 in x 2 1/2 in) |
| Weight | 0.48 kg | (1.1 lb) |
| Temperature operating storage | -10 °C to 50 °C -40 °C to 70 °C | (14 °F to 122 °F) (-40 °F to 158 °F) |
| Relative humidity | 0 % to 95 % non-condensing | |

STANDARD ACCESSORIES

User guide, Certificate of Calibration, instrument stickers in six languages, AC adapter/charger, lithium ion battery, shoulder strap, carrying case.

LASER SAFETY



SPSB-EF SPECIFICATIONS

EXTERNAL LAUNCH MODE CONDITIONER SPECIFICATIONS

| Model | SPSB-EF-C30 |
|--|--|
| Total connector insertion loss (dB) ^d | < 1 |
| Fiber length ^e | 34m / 112 ft |
| Launch conditions ^f | Encircled flux compliant at 850 nm (guaranteed) at 1300 nm (typical) |
| Optical source for EF compatibility | FLS-600-12D, AXS-350-12D, FOT-930-12D, FTB-720-12D, FTB-7200D-12D, AXS-110-12D |
| Available connectors | SC to LC SC to SC |

NOTES

- Guaranteed unless otherwise specified. All specifications valid at 23 °C ± 1 °C.
- rms for FP lasers; and -3 dB width for LEDs (typical values for LEDs).
- After a 15-minute warm-up period, and using an APC connector on the power meter (except for multimode sources, for which a PC connector is used). Expressed as ± half the difference between the maximum and minimum values measured during the period.
- Using a 50 μm fiber at the input of the SPSB-EF
- To measure the first connector loss, reflection value of OTDR port must be -45 dB or better and a maximum pulse width of 100 ns.
- Compliant with TIA-526-14-B and IEC 61280-4-1 Ed. 2.0

GENERAL SPECIFICATIONS

| | | |
|-------------------------------------|------------------------------------|-------------------------------------|
| Size (H x W x D) | 165 mm x 165 mm x 40 mm | 6 1/2 in x 6 1/2 in x 1 9/16 in |
| Weight | 0.3 kg | 0.7 lbs |
| Temperature operating storage | -10 °C to 50 °C -40 °C to 70 °C | 14 °F to 122 °F -40 °F to 158 °F |
| Relative humidity | 0 % to 95 % non-condensing | |

ORDERING INFORMATION

FLS-600-NS1548-XX-XX-XX

Model

12C = 850/1300 nm LED source 50/125 µm
12C-23BL = 850/1300 nm LED source 50/125 µm, 1310/1550 nm laser source 9/125 µm

Multimode Connector^a

EI-EUI-91 = UPC/SC
EI-EUI-98 = UPC/LC

Singlemode Connector^b

EI-EUI-28 = UPC/DIN 47256
EI-EUI-76 = UPC/HMS-10/AG
EI-EUI-89 = UPC/FC narrow key
EI-EUI-90 = UPC/ST
EI-EUI-91 = UPC/SC
EI-EUI-95 = UPC/E-2000
EI-EUI-98 = UPC/LC
EA-EUI-28 = APC/DIN 47256
EA-EUI-89 = APC/FC narrow key
EA-EUI-91 = APC/SC
EA-EUI-95 = APC/E-2000
EA-EUI-98 = APC/LC

Example: FLS-600-NS1548-12C-23BL-EI-EUI-91-EA-EUI-91

SPSB-EF-XX-XX

Model

C30 = Encircled flux external launch conditioner, multimode fiber 50/125 µm, 34 meters including pigtailed

Connector^c

91- 91 (SC/UPC to SC/UPC)
91- 101 (SC/UPC to LC/UPC)

Example: SPSB-EF-C30-91-101

Notes

- a. For multimode port
- b. For singlemode port
- c. First connector to source port must be SC-UPC only

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at www.EXFO.com/specs.

In case of discrepancy, the Web version takes precedence over any printed literature.